

# Troldtekt<sup>®</sup> acoustic panels

## Data sheet

### THE PRODUCT – TROLDTEKT ACOUSTIC PANELS

Troldtekt are cement-bonded wood wool panels made from wood and cement. The product consists of wood (spruce) which is shredded into wood wool and mixed with cement. We offer PEFC (PEFC/09-31-030)-certified or FSC<sup>™</sup> (FSC<sup>™</sup> C115450)-certified spruce. Both certifications ensure that the wood comes from responsible forestry operations and other controlled sources.

Troldtekt can be surface-treated, but is often used untreated. Due to the nature of the material, colour variations may occur with natural wood and natural grey (FUTURECEM<sup>™</sup>). To achieve an even distribution of the colour tones, we recommend mixing the panels during installation

Among the factors affecting colour variations are water/cement ratio, water content of the wood, drying rate, steam curing and curing moisture.

### PRODUCT STANDARDS, LABELLING AND CERTIFICATION

#### CE-marking

Within the EU, all building materials are legally required to be CE-marked. The CE-mark indicates that the building material can be legally sold and that it complies with the product standard to which the mark refers. Troldtekt products are CE-marked, and in addition to the marking we state:

Name of producer  
Troldtekt A/S

Certifications  
0615-CPR-222958G  
0615-CPR-80474G

Product standard number  
EN 13168:2012+A1:2015 and  
EN 13964:2014

Declaration  
See product data on page 2

#### Other approvals

Cradle to Cradle: Troldtekt is Cradle to Cradle-certified at Gold level. Troldtekt acoustic panels are documented as being free of harmful substances and can therefore safely be returned to the biological cycle. Additionally, waste from the production of Troldtekt acoustic panels is returned to the technical cycle and used as a resource in new cement at Aalborg Portland.



Indoor climate labelling: Troldtekt is indoor climate-labelled in the best degassing and particle release categories.



M1 classification: Troldtekt is M1-classified by the Finnish Building Information Foundation RTS sr. This is the best category, and means that the panels have an extremely low emissions level for volatile organic compounds (VOC).



Blue Angel: Troldtekt is eco-labelled under the German Blue Angel eco-labelling scheme, which guarantees that the product has a low impact on the environment and the climate and meets high standards for health protection.



PEFC and FSC: Troldtekt is PEFC (PEFC/09-31-030)- and FSC<sup>™</sup> (FSC<sup>™</sup> C115450)-certified, which means that all our products are manufactured using wood from responsible forestry operations and other controlled sources.



Light reflection: Light reflection for different types of Troldtekt panels (measured by Teknologisk Institut, Denmark) can be found on Troldtekt's webpage. Please scan the QR code.



## USE AND MAINTENANCE

Trolldtekt panels usually require no subsequent care. However, we recommend regular cleaning along with other surfaces – and otherwise as required. Light cleaning of the panels is easy using a

vacuum cleaner with a brush nozzle. Should vacuum-cleaning prove insufficient, you can wipe the panels using a lightly damp cloth. If you subsequently want to paint the Trolldtekt ceiling, you can use a hand

sprayer. Water-based paint will not reduce the sound-absorbing performance of the panels.

## RECYCLING

The entire range of Trolldtekt cement-bonded wood wool panels are Cradle to Cradle-certified in the gold category.

Consequently, we have complete documentation of the substances in the products, and documentation that the

products can be composted and safely returned to nature as a soil conditioner.

The cement in Trolldtekt's acoustic panels boosts oxygen levels during the composting process, while the wood adds organic material to the compost.

## TOLERANCES

It is important to note that Trolldtekt consists of the natural material wood - together with cement extracted from Danish mineral resources. The very nature of the material composition – wood wool

and cement – will incur small variations in the panels. Panel dimensions remain inside the tolerance indicated at 23 +/- 2 °C and 50 +/- 5 % relative humidity. However, inappropriate storage and lack

of acclimatisation could alter panel dimension and weight. It is therefore important that you observe the installation, storage and acclimatisation instructions carefully.

## PRODUCT DATA

The table below indicates the tolerances declared by us in accordance with EN 13168:2012+A1:2015, the standard for cement-bonded wood wool and double-layer panels with cement-bonded wood wool, and EN 13964:2014, the standard for suspended ceilings.

### Properties:

DIMENSIONS	
Width (mm)	600
Length (mm)	600/1200/2400
Thickness (mm)	25 35
Weight (kg/m <sup>2</sup> )	
Fine	10.6 13.9
Ultrafine	11.4 15.2
Extreme fine	11.7 15.5
TOLERANCES	
Length (mm)	> 1250 : ±2.0
	≤ 1250 : ±1.0
Width (mm)	±1.0
Thickness (mm)	Length > 1250 : ±2.0
	Length ≤ 1250 : ±1.0
Perpendicularity (mm/m)	± ≤ 2

FIRE	
Reaction to fire acc. to EN 13501-1:2018	B-s1,d0
Fire resistance capability acc. to EN 13501-2:2023	K <sub>1</sub> 10/K <sub>2</sub> 10
Cladding class	K <sub>1</sub> 10/B-s1,d0

IMPACT RESISTANCE	
Ball impact certification	1A

SUBSTANCES	
Chloride %	≤ 0.06
Formaldehyde	E1*

INDOOR CLIMATE	
Degassing	10 days
Particle release	Low

STANDARD	
Declared in accordance with	EN 13168:2012+A1:2015 EN 13964:2014

\* No measurable formaldehyde emission



This document reflects Trolldtekt's knowledge of certifications, standards, and products at the time of publication.

No rights can be derived from this document. Changes, typesetting and printing errors reserved.

The most recent version can be found online by scanning the QR code.

FEBRUARY 2026 COM V01

Trolldtekt A/S  
Sletvej 2A  
DK-8310 Tranbjerg J  
Tel. +45 8747 8100  
info@trolldtekt.dk  
www.trolldtekt.com